

BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 December 2004 (02.12.2004)

PCT

(10) International Publication Number
WO 2004/103744 A1

(51) International Patent Classification: B60F 3/00

Roger [GB/GB]; 23 Station Road, Llangelech, Llanelli, Carmarthenshire SA14 8UD (GB).

(21) International Application Number:
PCT/GB2004/002165

(74) Agents: PLUCKROSE, Anthony, William et al.; Boul
Wade Tennant, Verulam Gardens, 70 Gray's Inn Road, Lon-
don WC1X 8BT (GB).

(22) International Filing Date: 19 May 2004 (19.05.2004)

(25) Filing Language: English

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, HT, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(26) Publication Language: English

(30) Priority Data:
0311500.3 19 May 2003 (19.05.2003) GB

(71) Applicant (for all designated States except US): GIBBS
TECHNOLOGIES LIMITED [GB/GB]; Avenue Road,
Nuneaton, Warwickshire CV11 4LY (GB).


(72) Inventors; and

(75) Inventors/Applicants (for US only): PEIRCE, Ian,
Richard [GB/GB]; 7 Lake Road, Chiddlers Ford, Has-
leigh, Hampshire SO53 1EZ (GB). PEASE, Mathew,

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW).

[Continued on next page]

(54) Title: A HULL FOR AN AMPHIBIOUS VEHICLE



(57) Abstract: Marine vessel hull (11), with reference to figs. 1-3, is fit-
ted with one or more laterally spaced strakes (14, 15), and optional keel (16).
Each strake forward end may be triangular in cross-section (fig. 2), while each
rearward end is quadrilateral in cross-section (fig. 3). Each strake may extend
along most of the length of the hull; but not below the bottom of a keel. The
strakes may extend over removable panels in the hull underside. A section
of each strake may be formed integrally with the hull; with another section
formed separately, then affixed to the hull. The arrangement of strakes is par-
ticularly suitable to a planing amphibious vehicle with a low hull deadrise, as
the strakes have little effect on ground clearance, but act as hydrodynamic aids
on water. A forward triangular section allows turning in displacement mode,
but the aft section resists turning in both displacement and planing modes.

WO 2004/103744 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GR, GU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GI, GM, KE, LS, MW, MZ, NA,

- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

10/557759

IAP15 Rec'd PCT/PTO 18 NOV 2005

WO 2004/103744

PCT/GB2004/002165

A HULL
FOR AN AMPHIBIOUS VEHICLE

5 The present invention relates to a hull and, in particular, to a hull for an amphibious vehicle.

10 The designers of planing hulls for watercraft usually adopt a deadrise angle of between 14 and 18 degrees amidships. The angle may flatten along the run aft to 2.5 to 4 degrees at the transom. The applicant has determined that for an amphibious vehicle with a planing hull it is desirable to have a maximum deadrise angle of about 6 degrees on the planing surface in order to provide for adequate ground clearance when the vehicle is used on a road. Such a low deadrise angle
15 detrimentally affects directional stability of a hull when planing on water. In order to address this problem, the applicant provides a pair of strakes running lengthwise along the underside of the hull in order to improve directional stability of the hull when planing on water.

20 Normally it is only slow speed displacement vessels that use a smooth hull without hydrodynamic aids. Traditionally, a keel is a protrusion from the smooth under surface of a hull along its longitudinal centre line. This definition dates back
25 to the days of wooden ships, when the keel was the first part of the ship to be laid down during its build.

30 More recently, the term keel has been applied to one, or a pair of, deep fin(s) which extend downwards from a hull on, or on either side of, its longitudinal centre line. Such fins are also known as skegs, and are particularly popular on sail driven vehicles, from windsurfers to yachts; where their depth can provide great stability against lateral wind forces.

35 Strakes are relatively shallow structures, of similar depth to a central, full length, keel; but laterally displaced to either side of a vessel's longitudinal centre line.

Skegs are readily distinguished from strakes, in that:

- a) skegs are only about one quarter the length of the hull, whereas strakes extend along substantially the full hull length;

- b) skegs are themselves of greater depth to the rest of the hull structure - considerably deeper in the case of a windsurfer - whereas a strake would typically be less than 10% as deep as the rest of the hull;
- c) skegs are rarely, if ever, fitted to amphibious vehicles; because they would nullify ground clearance, and because amphibians are not generally wind powered.

Amphibious vehicles operating in displacement mode are limited to a speed of around six knots. At such speeds, which hold little marketing appeal, hydrodynamic aids have little effect; and the vessel remains substantially level when turning. A planing amphibious vehicle, however, may travel on water at 15 knots or more, and will lean into corners; so strakes can be useful hydrodynamic aids.

Keels and strakes are particularly useful for vessels driven by water jets, which have no dependent structures below the general level of the hull. By contrast, the drive pod, propeller, and rudder of an outboard motor can act as lateral stabilizers.

The present invention provides in a first aspect a hull for an amphibious vehicle with an underside submersible in water and at least one strake extending lengthwise along at least part of the underside, wherein the strake at least in part has a pair of surfaces which both extend downwardly from the hull at an angle of 75 degrees to 90 degrees to horizontal when the hull is level, each of the surfaces when immersed in water capable of giving rise to a lateral force on the hull during turning of the hull in water.

The present invention provides in a second aspect a hull for an amphibious vehicle with an underside submersible in water and at least a first pair of strakes extending parallel to each other lengthwise along at least part of the underside, wherein each strake at least in part has a pair of surfaces which both

extend downwardly from the hull at an angle of 75 degrees to 90 degrees to the horizontal when the hull is level, each of the surfaces when immersed in water capable of giving rise to a lateral force on the hull during turning of the hull in water.

5 The two strakes of said pair are preferably located one each on either side of a keel provided centrally on the underside of the hull, the strakes being spaced equidistantly from the keel.

The strakes of the prior art have been provided in parallel extending pairs on the underside of a hull, but have been triangular in cross-section so that each strake has one side inclined to provide a significant resistive transverse force during turning, but with the other side inclined to provide little resistive transverse force during turning. In

10 the present invention both sides of each strake are used to provide a significant resistive transverse force.

Preferably the or each strake has a forward part which is substantially triangular in transverse cross-section and a rearward section which is substantially quadrilateral in transverse cross-section. The or each section has a pair of surfaces each capable of giving rise to a lateral force, but said forces are greater, and more evenly balanced, at the rearward section.

20

It is preferable to have only at the rear of the hull a strake with a pair of sides capable of giving rise to greater resistive transverse forces, because otherwise the hull will be difficult to turn in water when not planing. It is only the rear of the underside of the hull which remains immersed in water when the hull is planing.

25

30

Preferably the or each strake extends along the majority but not the complete length of the underside of the hull.

35

Preferably the or each strake does not extend lower than the lowest part of a keel of the hull. Where the hull has removable panels then the or each strake can extend over the panels.

The or each strake can have a section formed integrally

with the hull and a section formed independently of the hull and then fixed to the hull. The said independently formed sections can be forward or rearward removable sections, so as to ease replacement when damaged. An independently formed section can
5 extend over a removable panel in the underside of the hull and can be removable to allow removal of the removable panel.

A preferred embodiment of hull according to the present invention will now be described by way of example only with
10 reference to the accompanying drawings, in which:

Figure 1 is a plan view of an underside of a hull according to the present invention;

Figure 2 is a perspective view from below of the hull of Figure 1

15 Figure 3 is a cross-section through the hull of Figure 1 taken along the line x-x';

Figure 4 is a cross-section through the hull of Figure 1 taken along the line y-y';

20 Figure 5 is a detail view of the cross-section of Figure 3; and

Figure 6 is a detail view of the cross-section of Figure 4.

In Figures 1 and 2 there can be seen a hull 11 of an
25 amphibious vehicle 10 having a forward bow end 12 and rear stern end 13. The underside of the hull 11 is shown and provided on the underside are a pair of strakes 14, 15 spaced equidistantly from a keel 16. Each strake 14, 15 runs lengthwise along the underside of the hull 11 for the majority of, but not the whole
30 length of, the hull 11. The underside of the hull 11 is provided with removable panels 7, 8, 17, 18 which are hydrodynamic aids (planing plates) as described in the applicant's co-pending UK patent application no. 0311499.8 entitled 'A Hull For An Amphibious Vehicle'. One section of
35 each strake 14, 15 is formed integrally with the hull 11 and another section formed integrally with, or assembled to, one of the removable panels 17, 18.

The forward sections of the strakes 14, 15 are triangular

in cross-section, as can be seen in Figure 3, and in detail for strake 14 in Figure 5, Figure 5 being an enlarged view of part of the cross-section of Figure 3, showing strake 14 in detail. Looking at Figure 5, it can be seen that the strake 14 has a face 19 which extends at an angle α of approximately 50 degrees to the horizontal when the hull is level and a face 20 which extends at an angle β of approximately 15 degrees to the horizontal when the hull is level. When the strake 14 moves through the water in the direction of arrow 21 at a first speed then interaction of the face 19 with the water gives rise to a transverse force of a first magnitude on the hull resisting the motion. When the strake 14 moves through the water in the direction of the arrow 22 at the same first speed then interaction of the face 20 with surrounding water gives rise to a transverse force of a second magnitude smaller than the first magnitude, due to the fact that the faces 19 and 20 lie at different angles to the horizontal.

The strake 15 is a mirror image of the strake 14. It too has faces inclined at different angles. Strakes 14 and 15 are shown with rounded corners between faces 19 and 20. This aids demoulding, particularly in series production. If it is desired that any part of strakes 14 and 15 which is not immersed in water should act as a spray rail, it may be moulded with a sharp corner between the inclined faces.

The rearward sections of the strakes 14, 15 are quadrilateral in cross section, as can be seen in Figure 4 and in detail for strake 15 in Figure 6, Figure 6 being an enlarged view of part of the cross-section of Figure 4, showing strake 15 in detail. Looking at Figure 6 it can be seen that the strake has a face 23 which extends at an angle γ of approximately 82 degrees to the horizontal when the hull is level and a face 24 which extends at an angle θ of approximately 85 degrees to the horizontal when the hull is level. Alternatively, angles γ , θ may be substantially equal, say 85 degrees. Indeed, angles γ , θ could be any angle from 75 to 90 degrees. The interaction of the face 23 with water gives rise to a significant resistive lateral force when the strake moves in the direction of the arrow 25 and

the interaction of the face 24 with water gives rise to a significant resistive lateral force when the strake moves in the direction of the arrow 26. Strake 14 is of the same cross-section as strake 15, but in mirror image thereto.

5

The quadrilateral shaped sections of the strakes 14, 15 give the hull good turning characteristics since the strakes together present a pair of faces giving rise to lateral forces on the hull for each sense of rotation of the hull, one face being provided by each strake. However, the hull does not provide excessive resistance to turning when the hull is not planing because of the triangular cross-section shape of the forward sections of the strakes 14, 15.

10

The rearward sections of the strakes 14, 15 can be made independently of the hull 11 and then be fixed to the hull 11. These sections may suffer from wear in use and thus can be made replaceable. They can also be made removable to allow removal of the removable panels 17 and 18.

15

It is preferable that the keel 16 is replaceable and takes the majority of wear during road use of the vehicle, as disclosed in the applicant's co-pending application no. GB0226443.0. The strakes 14 and 15 preferably do not extend lower than the keel 16 so that the keel preferentially receives ground impacts suffered by the hull in road use rather than the strakes 14, 15.

20

Whilst in the preferred embodiment described above two strakes 14, 15 are provided on the underside of hull 11, it will be appreciated that just one strake or indeed an array of strakes may be beneficially employed. Also, the location of strakes may be varied. Furthermore, whilst the section of the strakes in the preferred embodiment reduces from root to tip (i.e. the faces taper/converge to some degree), it is envisaged that alternative embodiments of hull according to the present invention could beneficially employ strakes whose section increases from root to tip (i.e. the faces diverge, of so-called 're-entrant' form). This may be achieved with integrally

25

30

WO 2004/103744

PCT/GB2004/002165

- 7 -

moulded strakes or independent strakes which are assembled or are retrofit additions.

5 Where the hull is used on an amphibious vehicle, the strakes may be located inboard of wheel arches in the hull. The road wheels may be mounted on retractable suspensions as is known in the amphibious vehicle art, so that the wheels can be retracted on water to reduce hydrodynamic drag.

WO 2004/103744

PCT/GB2004/002165

- 8 -

CLAIMS

1. A hull for an amphibious vehicle with an underside submersible in water and at least one strake extending
5 lengthwise along at least part of the underside, wherein the strake at least in part has a pair of surfaces which both extend downwardly from the hull at an angle of 75 degrees to 90 degrees to the horizontal when the hull is level, each of the surfaces when immersed in water capable of giving rise to a lateral force
10 on the hull during turning of the hull in water.
2. A hull for an amphibious vehicle with an underside submersible in water and at least a first pair of strakes extending parallel to each other lengthwise along at least part
15 of the underside, wherein each strake at least in part has a pair of surfaces which both extend downwardly from the hull at an angle of 75 degrees to 90 degrees to the horizontal when the hull is level, each of the surfaces when immersed in water capable of giving rise to a lateral force on the hull during
20 turning of the hull on water.
3. A hull as claimed in claim 2 wherein the strakes of the said pair of strakes are located one each on either side of a keel provided centrally on the underside of the hull, the
25 strakes being spaced equidistantly from the keel.
4. A hull as claimed in any one of the preceding claims wherein the or each strake has a forward part which is substantially triangular in transverse cross-section and a
30 rearward section which is substantially quadrilateral in transverse cross-section.
5. A hull as claimed in any one of the preceding claims wherein the or each strake extends along the majority of and not
35 the complete length of the underside of the hull.
6. A hull as claimed in any one of the preceding claims wherein the hull has a keel and the or each strake does not extend lower than the lowest part of the keel.

7. A hull as claimed in any one of the preceding claims wherein the underside of the hull has a plurality of removable panels and at least one strake extends over at least one removable panel.
8. A hull as claimed in any one of the preceding claims wherein at least one section of the or each strake is formed integrally with the hull.
9. A hull as claimed in any one of the preceding claims wherein at least one section of the or each strake is formed independently of the hull and then fixed to the hull, the said section of strake being a rearward section of the strake.
10. A hull as claimed in claim 8 wherein at least one section of the or each strake is formed independently of the hull and then fixed to the hull, the said section of strake being a forward section of the strake.
11. A hull as claimed in claim 9 or claim 10 wherein at least one independently formed section of strake is located extending over a removable panel in the underside of the hull so that the independently formed section of strake can be removed to permit removal of the removable panel.
12. A hull as claimed in any one of the preceding claims which has a planing surface and a maximum deadrise angle on the planing surface of 6 degrees.
13. A hull as claimed in any one of the preceding claims wherein the pair of surfaces of at least one section of the at least one strake are convergent such that the section of the strake reduces from root to tip.
14. A hull as claimed in any one of the preceding claims wherein the pair of surfaces of at least one section of the at least one strake are divergent such that the section of the strake increases from root to tip.

15. A hull as claimed in any one of the preceding claims which can be propelled through water to a speed where sufficient hydrodynamic lift is achieved for the hull to plane.

5

16. Use of a hull as claimed in any one of the preceding claims as the hull of an amphibious vehicle.

17. An amphibious vehicle incorporating the hull as claimed in any one of claims 1 to 15.

10

18. An amphibious vehicle as claimed in claim 17 further comprising a jet drive used to propel the vehicle through water in a marine mode to a speed where sufficient hydrodynamic lift is achieved for the vehicle to plane.

15

19. A hull substantially as hereinbefore described with reference to or as shown in the accompanying drawings.


20. Use of a hull substantially as hereinbefore described with reference to or as shown in the accompanying drawings.


20

21. An amphibious vehicle substantially as hereinbefore described with reference to or as shown in the accompanying drawings.

25

FIG. 1.






WO 2004/103744

3/6

PCT/GB2004/002165

FIG. 3.




WO 2004/103744

4/6

PCT/GB2004/002165

FIG. 4.




WO 2004/103744

5/6

PCT/GB2004/002165

FIG. 5.




WO 2004/103744

PCT/GB2004/002165

6/6

FIG. 6.



INTERNATIONAL SEARCH REPORT

National Application No.
'GB2004/002165

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 B60F3/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 B60F B63B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 025 010 A (SOOT OLAF) 24 May 1977 (1977-05-24)	1,2,8
Y	column 9, line 5 - line 15	3,6
A	column 10, line 1 - line 3 figures 3,4,7	4,5,7,9, 10,12-21
Y	----- GB 1 433 824 A (BEKAERT SA NV) 28 April 1976 (1976-04-28) figures 2,3 page 2, line 44 - line 55	3,6
A	----- US 2 370 508 A (WILKIE LEIGHTON A) 27 February 1945 (1945-02-27) page 3, line 26 - line 48 figures 8,9 ----- -/--	1
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : 'A' document defining the general state of the art which is not considered to be of particular relevance 'E' earlier document but published on or after the international filing date 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another claim or other special reason (as specified) 'O' document referring to an oral disclosure, use, exhibition or other means 'P' document published prior to the international filing date but later than the priority date claimed 'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention 'X' document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone 'Y' document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. 'Z' document member of the same patent family		
Date of the actual completion of the international search 12 October 2004		Date of mailing of the international search report 20/10/2004
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer Cauderlier, F

Form PCT/ISA/210 (second sheet) (January 2004)

INTERNATIONAL SEARCH REPORT

International Application No.

GB2004/002165

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 186 086 B1 (MAULDIN CHARLES C ET AL) 13 February 2001 (2001-02-13) column 1, line 18 - line 34 -----	1
A	FR 1 311 468 A (VOELTZEL DANIEL, MORIN ANDRE) 7 December 1962 (1962-12-07) the whole document -----	1
A	US 4 348 195 A (LANTZ GEORGE H) 7 September 1982 (1982-09-07) the whole document -----	1

Form PCT/ISA/210 (continuation of second sheet) (January 2004)

page 2 of 2

INTERNATIONAL SEARCH REPORT

International Application No

GB2004/002165

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4025010	A	24-05-1977	US 3935606 A	03-02-1976
			US 3972544 A	03-08-1976
GB 1433824	A	28-04-1976	NL 7207677 A	10-12-1973
			BE 798109 A2	31-07-1973
			ES 192213 Y	16-12-1974
			FR 2187564 A1	18-01-1974
			IT 985303 B	30-11-1974
			JP 49049386 A	13-05-1974
			ZA 7303519 A	24-04-1974
US 2370508	A	27-02-1945	NONE	
US 6186086	B1	13-02-2001	NONE	
FR 1311468	A	07-12-1962	NONE	
US 4348195	A	07-09-1982	CA 1119895 A1	16-03-1982

Form PCT/ISA/210 (patent family annex) (January 2004)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.